

# Allure™ EC-Smart-Air Series

## Communicating sensors

---



## Overview

The Allure EC-Smart-Air Series communicating sensors combine a precise environmental sensing in a discrete and alluring enclosure: temperature, humidity and CO<sub>2</sub>.

Compatible with the ECL series LonWorks® Controllers, ECB series BACnet® Controllers and ECLYPSE™ series BACnet/IP and Wi-Fi Controllers, including the Smart Room Control solution.

## Features & Benefits

- The Allure EC-Smart-Air Sensor is wired to the dedicated subnet port on the controller which frees up controller inputs
- Both power and communications pass through a single Cat 5e cable for reduced installation costs and easier installation
- Included quick-link connectors accelerates installation time by up to 75% while at the same time reduces potential wiring errors.
- Versatile mounting options including dry way, or North American, European, Swiss, or Asian style switch box
- Patented ABC Logic self-calibration guarantees lifetime CO<sub>2</sub> calibration
- All models come with an on-board temperature sensor for a precise feedback based temperature control
- Humidity sensing to optimize ideal level of comfort
- CO<sub>2</sub> sensing increases energy efficiency as part of the demand-controlled ventilation strategy

# Model Selection

Example: Allure EC-Smart-Air-C

Series	Option
Allure EC-Smart-Air	[blank]: Temperature only -H: Humidity, Temperature -C: CO <sub>2</sub> <sup>1</sup> Temperature -CH: CO <sub>2</sub> <sup>1</sup> Humidity, Temperature

1. A controller can support a maximum of two communicating sensors equipped with a CO<sub>2</sub> sensor. Any remaining connected communicating sensors must be without a CO<sub>2</sub> sensor.

## Product Specifications

### Power Supply Input

Voltage	16 VDC maximum, Class 2
Power Consumption	At the connected controller, an additional 0.5 VA per CO <sub>2</sub> sensor model (peak consumption: 1.5 VA) and 0.25 VA per non-CO <sub>2</sub> sensor model

### Communications

Rate	38 400 bps
Communications	RS-485
Wiring	Cable length: 600 ft (180 m) maximum
Cable Type	T568B Cat 5e network cable, 4 twisted pairs
Connectors	<b>IN:</b> RJ-45 <b>OUT:</b> RJ-45 (pass-through for daisy chain connection to other room devices)

### Temperature Sensor

Type	10 kΩ NTC Thermistor
Range	41°F to 104°F (5°C to 40°C)
Accuracy	± 0.9°F (± 0.5°C)
Resolution	0.18°F (0.1°C)

### Humidity Sensor

Accuracy	±3%
Resolution	1%

### CO<sub>2</sub> Sensor

Measurement Range	0 to 2000 ppm
Operating Elevation	0 to 16000 ft (0 to 4877 m)
Warm-up Time	< 2 minutes (operational), 10 minutes (maximum accuracy)
CO <sub>2</sub> Accuracy <sup>1</sup>	400-1250 ppm ± 30 ppm or 3% of reading, whichever is greater 1250-2000 ppm ±5% of reading + 30ppm
Temperature Dependence	±0.11% FS per°F (0.2% FS per °C)
Stability	<2% of FS over life of sensor (15 years)
Pressure Dependence	0.135% of reading per mm Hg; software adjustable
Sensing Method	Non-dispersive infrared (NDIR) absorption Gold-plated optics
Calibration Method	Patented ABC Logic self-calibration algorithm

1. Tolerance based on span gas of ±2% and ABC Logic enabled.

### Mechanical

Dimensions (H × W × D)	4.60 × 3.30 × 0.99" (117 × 84 × 25 mm)
Shipping Weight	Models with CO <sub>2</sub> sensing: 0.346lbs (0.157 kg) Model without CO <sub>2</sub> sensing: 0.311lbs (0.141 kg)
Enclosure Material	ABS
Enclosure Rating	Plastic housing, UL94-V0 flammability rating
Color	white
Installation	Wall mounting through mounting holes (see figure on next page for hole positions) or switch box (North America / European / Asian / Swiss)


### Environmental

Operating Temperature	32°F to 122°F (0°C to 50°C)
Storage Temperature	-4°F to 122°F (-20°C to 50°C)
Relative Humidity	0 to 90% Non-condensing
Ingress Protection Rating	IP20
Nema Rating	1

### Standards and Regulations

CE Emission	EN 61000-6-3: 2007 + A1: ed.2011
CE Immunity	EN 61000-6-1: 2007
FCC	FCC rules part 15, subpart B class B
UL Listed (CDN & US)	UL 916 Energy Management Equipment CSA C22.2 No. 205-12 File number: E228719
RoHS	All materials and manufacturing processes comply with the RoHS directive
WEEE	All products are marked according to the Waste Electrical and Electronic Equipment (WEEE) directive





Specifications subject to change without notice.

ECLYPSE, Distech Controls, the Distech Controls logo, EC-Net, Allure, and Allure UNITOUCH are trademarks of Distech Controls Inc. BACnet is a registered trademark of ASHRAE; BTL is a registered trademark of the BACnet Manufacturers Association. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks is under license. All other trademarks are property of their respective owners.

©, Distech Controls Inc., 2015 - 2021 All rights reserved.

Global Head Office - 4205 place de Java, Brossard, QC, Canada, J4Y 0C4 - EU Head Office - ZAC de Sacuny, 558 avenue Marcel Mérieux, 69530 Brignais, France